

WIND

Ultrasonic Anemometer 2D

Part number: 4.382x.0x.xxx

More than 35 different measurement values are available, for ex.:

- Orthogonal wind velocity vectors (X- and Y-distance)
- Scalar wind velocity
- Wind direction
- Acoustic-virtual temperature
- Acoustic-virtual temperature of the orthogonal measurement distances (X- and Y-distance)
- Standard deviation of the vectorial wind velocity (X and Y-distance)
- Standard deviation of the scalar wind velocity
- Standard deviation of the wind direction
- Standard deviation of the acoustic-virtual temperature
- Wind velocity of the gust acc. to WMO
- Wind direction of the gust acc. to WMO



The instrument is especially suitable for the use in the fields of

- Meteorology
- Climatology
- Regenerative energy, wind energy plant
- Traffic engineering, aviation and navigation
- Pollutant dispersal
- Wind alarm devices, building construction and building safety
- Indoor flow measurement
- And in alpine field of application

The ultrasonic measurement principle allows, compared to the classic anemometers, an inertia-free measurement of running variable dimensions with highest precision and accuracy. It is especially suitable for the measurement of gust- and peak values.

The measurement values can be transmitted digitally and/or in analogue form.

The serial or analogue output of the data is carried out alternatively as instantaneous value or with selectable time frame.

If necessary, the sensor arms are automatically heated in case of critical ambient temperatures. The possibility of malfunction, caused by icing, is minimized.

Model no. 4.3820.3x.xxx, thanks to the additionally installed ultrasonic converter heating, is suitable even for the more difficult use in locations where frequently icing is to be expected

Specification

Part number: 4.382x.0x.xxx

Wind speed	
Measuring range	0 ... 85 m/s
Resolution	0.1 m/s (standard) 0.01 m/s (user defined)

Accuracy	±0.1 m/s rms (< 5 m/s) ±2 % rms (5 ... 85 m/s)
Wind direction	
Measuring range	0 ... 360 °
Resolution	1 ° 1 ° (standard) < 1 ° (user defined)
Accuracy	±1 ° @ WS 1 ... 60 m/s ±2 ° @ WS 60 ... 85 m/s
Virtual temp.	
Measuring range	-50 ... +80 °C
Resolution	0.1 K
Accuracy	±0.5 K @ WS < 35 m/s
Data output digital	
Interface	RS485 / RS422
Baudrate	1200 ... 921600 Baud
Data values	instant. values, average values, standard deviation
Output range	1 per 10 msec up to 1 per 60 sec
Status signals	heating, Meas section error, Temperature of meas section
Data output analog	
Wind speed	0 ... 20 mA 4 ... 20 mA 0 ... 10 V 2 ... 10 V
Stromausgang	max. 400
Wind direction	0 ... 20 mA 4 ... 20 mA 0 ... 10 V 2 ... 10 V
Voltage output	min. 4000
Resolution	16 bit
Data input analog (alternative)	
Channels	3
Resolution	16bit
Operating voltage	
Electronic	8 ... 78 V DC or 12 ... 55 V AC / 2.5 W
Heating	24 V AC/DC, typ 80 W
Heating	
Heated components	Sensor arms
General	
Bus operation	up to 98 sensors
Electr. connection	8 pol. connector
Mounting	on a mast tube 1,5''

Housing	stainless steel (V4A) AiSi316Ti
Protection	IP 67
Dimension	Ø 424 mm x 287 mm
Weight	2.5 kg

Versions

As per 4.382x.0x.xxx, but:

Product number 4.3820.00.300

Data output digital	
Baudrate	9600 Baud
Duplex mode	Full duplex
Data telegram	no independent telegram output

Product number 4.3820.00.340

Data output digital	
Baudrate	9600 Baud
Duplex mode	Full duplex
Data telegram	VDT-Telegram (Telegram2)
Output range	10 per 1 sec

Product number 4.3820.01.300

Data output digital	
Baudrate	9600 Baud
Duplex mode	Half duplex
Data telegram	no independent data output
Data output analog	
Type	3 x 0 ... 20 mA

Product number 4.3820.02.300

Data output digital	
Baudrate	9600 Baud
Duplex mode	Half duplex
Data telegram	no independent data output
Data output analog	
Type	3 x 0 ... 10 V

Product number 4.3820.01.310

Data output digital	
Baudrate	9600 Baud
Duplex mode	Half duplex
Data telegram	no independent data output
Data output analog	
Type	3 x 4 ... 20 mA

Product number 4.3820.01.310
Data output digital

Baudrate	9600 Baud
Duplex mode	Half duplex
Data telegram	no independent data output

Data output analog

Type	3 x 4 ... 20 mA
------	-----------------

Product number 4.3820.02.320
Data output digital

Baudrate	9600 Baud
Duplex mode	Half duplex
Data telegram	no independent data output

Data input analog

Input type	3 x 0 ... 10 V
------------	----------------

Product number 4.3820.02.323
Data output digital

Baudrate	9600 Baud
Duplex mode	Half duplex
Data telegram	no independent data output

Data input analog





Input type	1 x 0 ... 10 V 2 x 2 ... 10 V
------------	----------------------------------

Product number 4.3820.00.260
Data output digital

Baudrate	4800 Baud
Duplex mode	Full duplex
Data telegram	NMEA - Telegram
Output range	10 per 1 sec

Accessories

Product	Product name	Brief description
---------	--------------	-------------------

	<p>Ultrasonic Bird deflector 4.3800.90.000</p>	<p>The Ultrasonic Bird Deflector protects the ultrasonic anemometer against measurement faults, which might be caused by different species of birds.</p> <table border="1"> <tr> <td colspan="2">Data output digital</td> </tr> <tr> <td>Switching output</td> <td>max. 24 V AC/DC</td> </tr> <tr> <td colspan="2">Interface</td> </tr> <tr> <td>Type</td> <td>RS485</td> </tr> <tr> <td>Data format</td> <td>8N1</td> </tr> <tr> <td>Baud rate</td> <td>2400 ... 115200 Baud</td> </tr> <tr> <td colspan="2">General</td> </tr> <tr> <td>Power supply</td> <td>12 ... 24V DC 24 V AC</td> </tr> <tr> <td>Electr. connection</td> <td>cable gland</td> </tr> <tr> <td>Housing</td> <td>Polycarbonate</td> </tr> <tr> <td>Protection</td> <td>IP 65</td> </tr> <tr> <td>Weight</td> <td>0.2 kg</td> </tr> </table>	Data output digital		Switching output	max. 24 V AC/DC	Interface		Type	RS485	Data format	8N1	Baud rate	2400 ... 115200 Baud	General		Power supply	12 ... 24V DC 24 V AC	Electr. connection	cable gland	Housing	Polycarbonate	Protection	IP 65	Weight	0.2 kg
Data output digital																										
Switching output	max. 24 V AC/DC																									
Interface																										
Type	RS485																									
Data format	8N1																									
Baud rate	2400 ... 115200 Baud																									
General																										
Power supply	12 ... 24V DC 24 V AC																									
Electr. connection	cable gland																									
Housing	Polycarbonate																									
Protection	IP 65																									
Weight	0.2 kg																									
	<p>Device to refuse birds 507245</p>	<p>The device to refuse birds shall prevent smaller birds in the distance of the US transformer from sitting on the instrument, thus providing for an undisturbed operation.</p>																								
	<p>Connecting cable 50775x</p>	<p>Suitable cable for 4.3820/30/75/80/81</p> <ul style="list-style-type: none"> length: see versions <table border="1"> <tr> <td colspan="2">General</td> </tr> <tr> <td>Cable length</td> <td>see versions</td> </tr> <tr> <td>Cable</td> <td>PUR 4 x 0,75 +2x2x0,14 mm²</td> </tr> </table>	General		Cable length	see versions	Cable	PUR 4 x 0,75 +2x2x0,14 mm ²																		
General																										
Cable length	see versions																									
Cable	PUR 4 x 0,75 +2x2x0,14 mm ²																									
	<p>Bird spike 508396</p>	<p>The bird spike prevents bigger birds from resting in the measurement path between the ultrasonic transducers, providing an undisturbed operation.</p> <table border="1"> <tr> <td colspan="2">General</td> </tr> <tr> <td>Material</td> <td>V4A (AiSi 316L)</td> </tr> </table>	General		Material	V4A (AiSi 316L)																				
General																										
Material	V4A (AiSi 316L)																									
	<p>Northring for Ultrasonic anemometer 508696</p>	<p>The adapter is used for the north alignment of a Ultrasonic anemometer.</p> <table border="1"> <tr> <td colspan="2">General</td> </tr> <tr> <td>Length</td> <td>90 mm</td> </tr> <tr> <td>Material</td> <td>Alluminum anodized (AlMgSi1)</td> </tr> <tr> <td>Weight</td> <td>0.4 kg</td> </tr> <tr> <td>Fixing boring</td> <td>for mast Ø 50 mm for sensor Ø 50 mm</td> </tr> </table>	General		Length	90 mm	Material	Alluminum anodized (AlMgSi1)	Weight	0.4 kg	Fixing boring	for mast Ø 50 mm for sensor Ø 50 mm														
General																										
Length	90 mm																									
Material	Alluminum anodized (AlMgSi1)																									
Weight	0.4 kg																									
Fixing boring	for mast Ø 50 mm for sensor Ø 50 mm																									



Meteo-Online
9.1700.98.x01

Meteo-Online is a software for detecting, filing, and displaying data of meteorological measuring instruments. The display of the data is carried out graphically as diagram and/or as text. The user has the possibility to place the display-elements free on the screen, and to save them.

Data display	
Monitor - display	<ul style="list-style-type: none"> - Values - Diagrams - Tables - Windrose - Time - Date
Compatibility	
Connectable instruments	<ul style="list-style-type: none"> - US-Anemometer - Datalogger - Clima Sensor - Weather station WSC11 - Wind display - etc.
System requirements	PC mit <ul style="list-style-type: none"> - Prozessor > 1 GHz - RAM > 1 GB
Operating system	<ul style="list-style-type: none"> - Windows 2003 SP2 - Windows Server 2008 - Windows 7 - Windows Server 2008 R2 - Windows 7 SP1 - Windows Server 2008 R2 SP1 - Windows 8 - Windows 10

